

KP1-VDSL

**Krone Protector**



The Novaris KP series of products are suitable for telephone and signal line protection for termination systems utilising KRONE LSA-PLUS 10-way connection blocks. The KP10-VDSL provides protection for the highest VDSL2 signals with minimal attenuation and a 3dB frequency of 70MHz.

Telephone and Signal protection

The KP_x-T devices are designed for protecting PSTN and digital PABX signals with a maximum line voltage of up to 200V. The KP_x-xxDC product range has been engineered to protect all common signalling systems. A single KP10-xxDC can be used to efficiently protect up to 10 signal pairs.

1 Pair and 10 Pair Configurations





Choose your protection width based on the number of lines you need to protect.

Wiring**Dimensions****Standards**

No standards are mentioned!

Product Datasheet

Electrical Specifications

Connection type		Series
Number of lines		1 pair
Modes of protection		Transverse and Common
Maximum continuous voltage (DC)	U_c	230V
Maximum discharge current (8/20 μ s)	I_{max}	5kA
Maximum common mode discharge current (8/20 μ s)		10kA
Impulse durability C2 10x8/20 μ s		5kA
Maximum load current	I_L	250mA
AC durability 5x1s		1Arms
Overstressed fault mode		Mode 3
Response time	t_A	<5ns
Insertion loss @ 150 Ω		<0.5dB @ 20kHz
3 dB Frequency @ 150 Ω		70MHz












Electrical (L-L) Specifications

Voltage protection level @ 1 kV/ μ s	U_p	450V
Voltage protection level @ 100 V/ s		130V
Capacitance	-I-	1.5pF

Electrical (L-PE) Specifications

Voltage protection level @ 1 kV/ μ s	U_p	450V
Voltage protection level @ 100 V/ s		230V
Capacitance	-I-	1.5pF

Mechanical Specifications

Minimum operating temperature		-40°C
Maximum operating temperature		70°C
Minimum operating humidity		5%
Maximum operating humidity		95%
Mounting method		Krone LSA-Plus
Environmental rating		IP20
Enclosure material		Polycarbonate
Enclosure finish		Black EDM
Terminal type		Krone LSA-Plus
Length		53mm
Width		126mm
Height		21mm

Other Specifications

Product Code		KP1-VDSL
--------------	---	----------

Shipping Specifications

Weight		20g
Customs tariff		85363000